

# Arc

Arc brings a soft curve to hard edges and is suitable for commercial grade interiors. Modulo® MR Arc is outstanding for walls, ceilings and curves achieving a radius of 175mm.



Modulo® MR Arc shown in NAVURBAN™ Byron Blackbutt

## How to Specify

<b>Product</b>	Screenwood Modulo® MR
<b>Application</b>	Internal use only
<b>Substrate</b>	Moisture resistant MDF
<b>Fire</b>	Group 3
<b>Profile</b>	Arc
<b>Length</b>	Available lengths: 2.7m, 3.6m, 5.4m
<b>Finish</b>	Select finish (e.g. NAVURBAN™ Byron Blackbutt)

## Certifications

### Global GreenTag™ certified

Global GreenTag™ certified  
GreenTag Level B and GreenTag  
PHD Platinum HEALTH™.

### Fire certified

Group 3 fire-rated, tested to AS5637.1.

### PEFC™ Fibreboard

From environmentally certified Australian mills.

### Resistant to wear

NAVURBAN™ tested for abrasion resistance to AS 1580.

### Light Reflective Value

NAVURBAN™ tested for exposure in indoor applications to AS/NZS 1428.1.

### Low VOC

Exceeds GBCA requirements for commercial fitouts. Tested for organic emissions to ASTM D5116-2017.

### UV resistant

NAVURBAN™ tested for exposure in indoor applications to ASTM D4459.


Test results are available on request.



# Arc


## Profile detail

17.3kg/m<sup>2</sup>




## Concave curve

175mm Curve Radius




## Convex curve

175mm Curve Radius



## Concealed screw installation of Modulo® MR



Drawings not to scale.

# Arc




Visit [screenwood.com.au/finishes](https://screenwood.com.au/finishes)




Visit [screenwood.com.au/resources](https://screenwood.com.au/resources)

Mitre Corner Detail



Rebated Corner Detail



## Ultra-realistic Finishes

Modulo® is profile wrapped in premium NAVURBAN™ non-PVC olefin decorative film with seamless finish matching across Screenwood and NAVURBAN™ products. Low VOC, UV and abrasion resistant, no ongoing maintenance and a large scale pattern to avoid pattern repeat. For the latest finishes, please visit [screenwood.com.au/finishes](https://screenwood.com.au/finishes).

## Features

- For interior walls, ceilings and curves of up to 175mm radius
- Group 3 fire rated, Golbal GreenTag™ and PEFC certified
- Prefinished in olefin film for an ultra-realistic finish
- Low VOC, UV and abrasion resistant
- Simple to install and no ongoing maintenance
- Easy to order with a fast manufacturing lead time
- Arrives in recyclable packaging
- Designed and made in Australia by Screenwood
- Combine profiles to create a bespoke look



**Need to know more?  
We're here to help.**

[hello@screenwood.com.au](mailto:hello@screenwood.com.au)  
+61 2 9521 7200  
[screenwood.com.au](https://screenwood.com.au)