Soundlina®



Group 1 perforated architectural wall covering for superior fire protection, high acoustic comfort, and aesthetics.



Soundlina® finished in NAVURBAN Diamond™

How to Specify

Product Screenwood Soundlina®

Application Internal use only

Fire Group 1

NRC Up to 0.85

Substrate Perforated acoustic fabric*

Roll Size 600mm x 9850mm

Finish Select finish (e.g. NAVURBAN Diamond™ Toorak)

Certifications

Global GreenTag™ certified

Global GreenTag™ certified GreenTag Level B and GreenTag PHD Platinum HEALTH™.

Acoustic performance

Tested to achieve up to 0.85 NRC when installed as recommended.

Light Reflective Value

NAVURBAN™ tested for exposure in indoor applications to AS/NZS 1428.1.

UV resistant

NAVURBAN™ tested for exposure in indoor applications to ASTM D4459.

*A non-acoustic wallpaper version of Soundlina® is available exclusively through our trusted partner, New Age Veneers.

432 The Boulevarde

Kirrawee NSW 2229

Fire certified

Group 1 fire-rated, tested to AS/NZS 3837-1998.

Resistant to wear

NAVURBAN™ tested for abrasion resistance to AS 1580.

Low VOC

Exceeds GBCA requirements for commercial fitouts. Tested for organic emissions to ASTM D5116-2017.

Test results are available on request.







Version 1



Soundlina®



Range Overview

Effective cover 5.91m²
Weight 360g/m²






























Ceiling installation



- 1 Acoustic insulation
- 2 Perforated plasterboard (painted black)
- 3 Soundlina® perforated wall covering
- 4 Suspended ceiling system
- 5 Stud wall

Wall installation



Achieves 0.85 NRC when installed as recommended. For Installation Guide, visit screenwood.com.au/resources.



^{*}Pattern matching required for Classic American Oak as woodgrain features crown.