


Rectangular 4018 Series

An interior prefinished, preassembled acoustic linear batten system. Suitable for horizontal, vertical and curved applications.



Panels FR Rectangular 4018-8 shown in NAVURBAN™ Tablelands

How to Specify

Product	Screenwood Panels FR
Fire	Group 2
Profile	Rectangular 4018-6 /4018-7 /4018-8
Length	Cut to specified size from lengths of 2.4m and 3.0m
Finish	Select finish (e.g. NAVURBAN™ Byron Blackbutt)

Certifications

Global GreenTag™ certified

Global GreenTag™ certified
GreenTag Level B and GreenTag
PHD Platinum HEALTH™.

PEFC™ Fibreboard

From environmentally certified Australian mills.

Light Reflective Value

NAVURBAN™ tested for exposure in indoor applications to AS/NZS 1428.1.

UV resistant

NAVURBAN™ tested for exposure in indoor applications to ASTM D4459.

Acoustic performance

Achieves NRC of up to 1.0 when installed as recommended.

Fire certified

Group 2 fire-rated, tested to AS5637.1.

Low VOC

Exceeds GBCA requirements for commercial fitouts. Tested for organic emissions to ASTM D5116-2017.

Resistant to wear

NAVURBAN™ tested for abrasion resistance to AS 1580.




Rectangular 4018 Series

Standard set-outs

Rectangular 4018-6	Blade spacing	31.3mm	
	Weight	10.7kg/m ²	
Rectangular 4018-7	Blade spacing	24.3mm	
	Weight	12.5kg/m ²	
Rectangular 4018-8	Blade spacing	19mm	
	Weight	14.5kg/m ²	

Back view

End view



Drawings not to scale.