


Linea 40

Linea 40 is a wood panelling look-alike profile but is far easier, faster, and more cost effective to install than traditional panelling. It is designed to perform in Group 1 fire-rated and noise-sensitive interiors.



Modulo® Acoustic Linea 40 shown in NAVURBAN Silken™ Avalon Shore

How to Specify

Product	Screenwood Modulo® Acoustic
Application	Internal use only
Substrate	Aluminium
Fire	Group 1
NRC	0.75
Profile	Linea 40
Length	Available lengths: 2.7m, 3.6m, 5.4m
Finish	Select finish (e.g. NAVURBAN™ Balmoral)

Certifications

Acoustic performance

Achieves NRC 0.75 when installed as recommended.

Global GreenTag™ certified

All our products are Global GreenTag™ certified. As this one has just launched, certification for Modulo® Acoustic is underway to align with our ethical and sustainability goals.

Fire certified

Group 1 fire-rated, tested to AS5637.1 and AS/NZS 1530.3:1999.

Resistant to wear

NAVURBAN™ tested for abrasion resistance to AS 1580.

Light Reflectance Value

NAVURBAN™ tested for exposure in indoor applications to AS/NZS 1428.1.

Low VOC

Exceeds GBCA requirements for commercial fitouts. Tested for organic emissions to ASTM D5116-2017.

UV resistant


NAVURBAN™ tested for exposure in indoor applications to ASTM D4459.

Test results are available on request.

Linea 40


Profile detail

10.5kg/m²




Concave curve

300mm Curve Radius




Convex curve

300mm Curve Radius



Concealed screw installation of Modulo® Acoustic



Drawings not to scale.

Linea 40



Visit screenwood.com.au/finishes

Accessories

- Installation is simple with Screenwood start trim and external corner trim available to fit Modulo® Acoustic providing a professional finish.
- No costly componentry is required and can be combined with aluminium trims supplied by others.

Ultra-realistic Finishes

Modulo® is profile wrapped in premium NAVURBAN™ non-PVC olefin decorative film with seamless finish matching across Screenwood and NAVURBAN™ products. Low VOC, UV and abrasion resistant, no ongoing maintenance and a large scale pattern to avoid pattern repeat.

For the latest finishes, please visit screenwood.com.au/finishes.



Visit screenwood.com.au/resources

Features

- For interior walls, ceilings and curves of up to 300mm radius
- High acoustic performance
- Group 1 fire rated & Golbal GreenTag™ certification pending
- Prefinished in olefin film for an ultra-realistic finish
- Low VOC, UV and abrasion resistant
- Simple to install and no ongoing maintenance
- Easy to order with a fast manufacturing lead time
- Arrives in recyclable packaging
- Designed and made in Australia by Screenwood



Need to know more?

We're here to help.

hello@screenwood.com.au

+61 2 9521 7200

screenwood.com.au