

Panels Product Ranges

Different Panels profiles feature different substrates. Please follow the specific care instructions matching your installed substrate to maintain performance and validate your Warranty.

1. MDF Substrates

Applicable Profiles: Panels MR (Moisture Resistant) and Panels FR (Fire Retardant).

Panels featuring timber-based core substrates and premium NAVURBAN™ surfaces are designed for highly resilient internal wall and ceiling decoration.

- **Standard Cleaning:** Wipe surfaces down using a soft microfiber cloth dampened with warm water and a mild household dishwashing detergent. Always wipe in the direction of the woodgrain embossed structure for optimal streak-free results.
- **Testing Chemical Suitability:** If in doubt regarding a specific liquid formulation or commercial surface spray, verify compatibility with the chemical manufacturer first. Test the liquid on a hidden surface cut-off or small discrete area prior to wide application.
- **Spills and Splatters:** Accidental contact with harsh liquids must be addressed instantly. Wipe off immediately with a dry cloth and wash down carefully with fresh water. This includes accidental over-sprays from household ceramic cooktop cleaners, tile cleaners, bathroom chlorine bleach, or oven chemicals.
- **Prohibited Cleansers and Tools:** Strictly avoid solvents such as acetone or trichloroethylene. Do not use scouring powders, coarse abrasive pads, metal steel wool, or sandpaper. These destroy the non-PVC olefin wrap layer, inducing irreversible dulling and leaving the core raw and susceptible to staining.
- **Physical Protection:** Avoid dragging, knocking, or slamming heavy materials against the panels to prevent surface denting.

- **Testing Chemical Suitability:** If in doubt regarding a specific liquid formulation or commercial surface spray, verify compatibility with the chemical manufacturer first. Test the liquid on a hidden surface cut-off or small discrete area prior to wide application.
- **Spills and Splatters:** Accidental contact with harsh liquids must be addressed instantly. Wipe off immediately with a dry cloth and wash down carefully with fresh water. This includes accidental over-sprays from household ceramic cooktop cleaners, tile cleaners, bathroom chlorine bleach, or oven chemicals.
- **Prohibited Cleansers and Tools:** Do not use abrasive cleaners, pads or harsh solvents. Alcohol, ammonia and other light solvents may be used for tougher stains. If the panels are subjected to any moisture, please wipe them down immediately. Internal coatings should not be soaked or hosed as this will negatively impact the coating.
- **Physical Protection:** Avoid dragging, knocking, or slamming heavy materials against the panels to prevent surface denting.

Disclaimer

The information, opinions, advice, and recommendations provided have been prepared with due care. They are offered only for the purpose of providing useful and helpful assistance to specifiers and their clients. While every effort has been made to ensure that this is in accordance with current technology, it is not intended as an exhaustive statement of all relevant knowledge.

2. Solid Timber Substrates

Applicable Profiles: Panels Solid Timber

Panels Solid Timber profiles are manufactured from a range of PEFC timber species including Hemlock, Spotted gum, Blackbutt and Western red cedar, and are prefinished in satin-matte lacquer.

- **Standard Cleaning:** Periodic dusting will keep Screenwood Panels looking their best. If required, finished surfaces are easy to clean using a damp cloth with mild soap and warm water, or non-abrasive wood cleaning products.
Wipe surfaces down using a soft microfiber cloth dampened with warm water and a mild household dishwashing detergent. Always wipe in the direction of the woodgrain.